



Orlando's Investment in Stormwater Data Pays Dividends in Mapping Flood Risk across the City

FSA 2025 Annual Conference

Ft. Myers, FL | June 12, 2025

Max Wallace, PE, CFM (Drummond Carpenter)

Brett Cunningham, PE, ENV SP (Jones Edmunds)




Introduction

- **Takeaways**

- Advocating for change
- Demonstrating that the change is worthy

- **Three stages of change**

- Ridicule
- Recognition
- Acceptance



Source: Medium.com

Evolution of Watershed Planning

- **Key Feasibility Factors**

- Availability and quality of data
- Computing power



Evolution of Watershed Planning

- **Key Feasibility Factors**

- Availability and quality of data
- Computing power



Source: Medium.com




Source: AIBrilliance.com



Source: Medium.com


Model Data for Self-Build

- ✓ DEM
 - 2018 LiDAR (2.5-feet)
- ✓ Soils
 - SSURGO Soils (Green-Ampt)
- ✓ Land Cover
 - WMD
 - NOAA C-Cap Imperviousness
 - MS & Google Building Footprints
- ✓ Pipe network
 - City & County Stormwater GIS




TUFLOW as an Example

SIMPLIFIED INUNDATION MAPPING



TRADITIONAL 1D LUMPED MODEL

DETAILED LOCAL INUNDATION MAPPING




MODERN HIGH-RESOLUTION 2D MODEL

Source: www.com.hk

TUFLOW Attributes

- ✓ Full SWE (momentum & turbulence)
- ✓ Automated grid generation
- ✓ Sub grid sampling
- ✓ Seamless 1D integration
- ✓ GPU accelerated
- ✓ Automated high-resolution mapping
- ✓ Non- Proprietary Inputs & Outputs



Processes Eliminated


- ✗ Subbasin delineation
- ✗ Time of concentration (or similar)
- ✗ Imperviousness/curve number calculation
- ✗ Full model schematic
- ✗ Stage-area extraction
- ✗ GIS-model exchange
- ✗ Floodplain delineation

Bonus: No errors introduced in eliminated processes and QC not required for them



2D Pros and Cons

- Modeling Approach of the future?
 - Pros
 - Fast setup
 - High resolution
 - Accurate
 - Quick updates
 - Cons
 - Not widely used
 - Growing regulatory acceptance
- Still a place for traditional lumped models



A Need for Rapid City-wide Model

- Resilient Florida Planning Grant (23PLN24)
- **\$275k** approx. total project cost
- **1.5 year** estimated project duration
 - ~13 month of technical work
- City-wide flood depth estimates required
- Accurate representation of flood risk desired



Source: Patch.com

City Stormwater Infrastructure Survey




- Originally led by Jim Hunt and Rick Howard
- Initiated in 2009
- \$11.5M investment



Top movies at the box office
on June 12, 2009...

Now Iconic




City Stormwater Infrastructure Survey



- Collected in GIS framework
- View on [Public Utilities Data Portal](#)
- "This has paid for itself many times" - Orlando Staff

Component	Count / Length
Structures	61,499
Culverts	57,241 / 1,081 mi
Open channels	3,516 / 297 mi
Ponds	1,853
Pump Stations	22



Model Data

NOAA C-CAP Imperviousness

- 1-m resolution impervious mapping
- Available Statewide
- 2021 NAIP Imagery
- ~97% accuracy



MS/Google
2023 Building
Footprints
NOAA 2022
Waterbodies
NOAA 2021
Impervious

300


Feet

N

13


Model Domain

- ~450 sq. mi.
- ~7.1M computational cells
- City - 30ft / County - 60ft
- Over 100,000 1-D Features
- 20-40 hour runtime per sim per region
- Cost: \$2.1-6.8M → \$169k






Model Domain


- ~450 sq. mi.
- ~7.1M computational cells
- City - 30ft / County - 60ft
- Over 100,000 1-D Features
- 20-40 hour runtime per sim per region
- Cost: \$2.1-6.8M → \$169k




Calibration – Event Selection



Calibration - Example



Calibration - Summary




48 Gauges

- MAE – 0.62 ft
- RMSE – 0.82 ft
- < 1 ft – 87%
- Average NSE – 0.88 (excluding outliers)

Validation

- Media Reports of Flooding
- NearMap ImpactResponse Imagery
- Web Map City Review




Validation

- Media Reports of Flooding
- NearMap ImpactResponse Imagery
- Web Map City Review



Validation




- Media Reports of Flooding
- NearMap ImpactResponse Imagery
- Web Map City Review



Rainfall Change Factors (USGS & FFH)

Script Inputs/options

- Station, Basin, or County
- Downscaled GCM Dataset(s)
- 2040 or 2070 planning horizon
- Return period and duration
 - 5, 10, 25, 50, 100, 200, or 500-yr
 - 1-, 3-, or 7-day




Rainfall Change Factors (USGS & FFH)

Planning Horizon	Return Period	Duration	CMIP5					CMIP6	
			CORDEX	Jupiter WRF	LOCA	MACA	All Datasets	LOCA 2	NASA
2040	100-yr	1-day	1.23	1.11	1.105	1.355	1.18	1.055	1.07
		3-day	1.2	-	1.115	1.295	1.21	1.07	1.09
		7-day	1.16	-	1.25	1.33	1.245	1.055	1.13
	500-yr	1-day	1.2	1.1	1.15	1.46	1.18	1.055	1.05
		3-day	1.23	-	1.16	1.45	1.29	1.065	1.11
		7-day	1.23	-	1.32	1.565	1.305	1.075	1.175
2070	100-yr	1-day	1.29	1.24	1.05	1.435	1.34	1.075	1.095
		3-day	1.21	-	1.12	1.405	1.34	1.105	1.075
		7-day	1.18	-	1.17	1.48	1.34	1.135	1.16
	500-yr	1-day	1.26	1.26	1.065	1.655	1.44	1.075	1.02
		3-day	1.23	-	1.17	1.575	1.46	1.09	1.035
		7-day	1.26	-	1.24	1.785	1.485	1.165	1.175

18 - 46% (CMIP5) vs 2 - 10% (CMIP6) for durations studied in this VA
 Currently, FL Flood Hub seems to be favoring LOCA 2

Rainfall Change Factors – Unknowns

- Assumptions or compromises in selecting CFs
- Pending official recommendations (from FL Flood Hub)
 - Station, County, or Climate Region Scale
 - CMIP5 vs CMIP6 (number/detail of GCMs, review)
 - NOAA Atlas 15 recommendations
- Uncertainty
 - GCMs can struggle with rain/tropical cyclone path
 - Are Small CFs appropriate in VA context?
 - Will rainfall distribution/regions change?
 - Future development
 - “Acceptable” flood risk



Critical Assets – Statewide Dataset



Transportation & Evacuation Routes



Critical Infrastructure

- Airports
- Bridges
- Bus Terminals
- Ports
- Major Roadways
- Marinas
- Rail Facilities
- Railroad Bridges




Community & Emergency Facilities

- Schools, Colleges, and Universities
- Community Centers
- Disaster Recovery Centers
- Emergency Medical Service Facilities
- Emergency Operations Centers
- Fire Stations
- Health Care/Hospitals
- Law Enforcement Facilities
- Local and State Government Facilities
- Logistical Staging Areas
- Affordable Public Housing
- Risk Shelter Inventory




Natural, Cultural & Historical


- Conservation Lands
- Parks
- Shorelines
- Surface Waters
- Wetlands
- Historical and Cultural Assets



Critical Assets – Gaps



- 1. Spatial Gaps
- 2. Underrepresented Type/Subtype
- 3. Duplicate Information
 - a) Duplicate GIS features
 - b) Overlap across types
- 4. Outdated Information
- 5. Incorrect Location



FACILITY_I	FACILITY_N	FACILITY_T	OBJECT_OF_
83717	DEROCHE BUILDING SUPPLY, INC DBA CROSSROADS B...	Solid Waste	Facility
83717	DEROCHE BUILDING SUPPLY, INC DBA CROSSROADS B...	Solid Waste	Waste Processing Area

Critical Assets – Gap Rectification


11,379 → 76,350 assets

+64,971 (+571%)

15% in statewide dataset

Large Net Increase	<ul style="list-style-type: none"> • Stormwater • Hydrants • Wetlands
Large Relative Increase	<ul style="list-style-type: none"> • Parks • Emergency Operation Center • Military Installations
New Asset Types	<ul style="list-style-type: none"> • Food Security (SNAP retailers and farms) • Fueling stations (gas and EV)
Net Losses	<ul style="list-style-type: none"> • Reclassification • Duplicate points • Tracked under another type

Sensitivity Criteria




Summary of Impacts (PRELIMINARY)

Sensitivity to Future Rainfall (100-yr Current to 2070)	Critical Assets
Number Increase	<ul style="list-style-type: none"> • Stormwater structures • Hydrants • Historical Structures
Relative Increase	<ul style="list-style-type: none"> • Historical Structures • Gas stations • Colleges and Universities • Solid Waste Facilities • EV Charging Hubs • Water Tanks • Community Centers

What's next?

1. Complete Final VA
2. Floodplain Management Plan for CRS credits
3. Rapidly assess alternatives and identify future projects/grants
4. New frontier with high-performance models & AI



Conclusions

1. Investments in stormwater data (GIS, monitoring) WILL pay off in unforeseen ways
2. High performance computational models can now be incorporated into a single desktop to dramatically increase detail and accuracy of flood models at a fraction of the cost
3. Florida's understanding of flood risk is rapidly improving, and will help address the problems of recent storm intensification and recurrence

In Memory of Jim Hunt



- Deputy Public Works Director – City Engineer
- FSA President (2013-14)
- FSA's Volunteer Service Award named in his honor

